

17

UTILITY
PATENT APPLICATION
TRANSMITTAL

Date: **January 6, 2000**

010

22

EL176999117US

jc:564 U.S.

01/06/00

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, D.C. 20231

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission
(If applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to Computer Copy)
 - c. ☐ Statement verifying identity of above copies

- Descriptive title of the invention
- Cross References to Related Applications
- Statement Regarding Fed. Sponsored R&D
- Reference to Microfiche Appendix
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claims
- Abstract of the Disclosure

3. ☐ Drawings (35 U.S.C. 113) Total Sheets ☐
4. ☒ Oath or Declaration Total Pages ☐ [2]

- a. ☒ Newly Executed (original or copy)
b. ☐ Copy from a prior application (37 C.F.R. 1.63(d) - for continuation/divisional with Box 18 completed)

[Mark Box 5 below]

- ### **I. DELETION OF INVENTOR(S)**

Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. 1.63(d)(2) and 1.33(b)

5. ☐ Incorporation by Reference (useable if Box 4b is checked). The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☒ 37 C.F.R. 3.73(b) Submission
- ☒ Power of Attorney
10. ☐ English Translation Document (*if applicable*)
11. ☐ Information Disclosure Statement with
Copies of Citations as necessary
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (*Should be specifically itemized*)
14. ☐ Small Entity Statement(s)
- ☐ Statement filed in Prior Application. Status still proper and
desired
15. ☐ Certified Copy of Priority document(s)
(*If foreign priority is claimed*)
16. ☒ File Data Sheet
17. ☐ Other

18. If a **CONTINUING APPLICATION**, check appropriate box and supply the requisite information:
☐ Continuation ☐ Division ☐ Continuation-in-part (CIP) of prior Application No. _____

19. CORRESPONDENCE ADDRESS

ATTY NAME
AND REG. NO.

**Z. Peter Sawicki;
30,214**

SIGNATURE:

E: J. P. S. Smith

ADDRESS

Kinney & Lange, P.A.
THE KINNEY & LANGE BUILDING
312 South Third Street
Minneapolis, MN 55415-1002

TELEPHONE

(612) 339-1863

FAX

(612) 339-6580

Inventor Information

Inventor One Given Name :: Donald G.
 Family Name :: Dahlstrom
 Name Suffix ::
 Postal Address Line One :: 4455 North Pine Tree Road
 Postal Address Line Two ::
 City :: Oneida
 State/Province :: WI
 Country ::
 Postal or Zip Code :: 54155
 City of Residence :: Oneida
 State/Prov. of Residence :: WI
 Country of Residence ::
 Citizenship :: U.S.A.

Inventor Two Given Name :: James
 Family Name :: Wiegand
 Name Suffix ::
 Postal Address Line One :: 2nd Pleasantview Lane
 Postal Address Line Two ::
 City :: Circle Pines
 State/Province :: MN
 Country ::
 Postal or Zip Code :: 55014
 City of Residence :: Circle Pines
 State/Prov. of Residence :: MN
 Country of Residence ::
 Citizenship :: U.S.A.

Inventor Three Given Name :: William R.
 Family Name :: Aimutis
 Name Suffix :: Jr.
 Postal Address Line One :: 3126 Rodeo Drive N.E.
 Postal Address Line Two ::
 City :: Blaine
 State/Province :: MN
 Country ::
 Postal or Zip Code :: 55449
 City of Residence :: Blaine
 State/Prov. of Residence :: MN
 Country of Residence ::
 Citizenship :: U.S.A

Correspondence Information

Name Line One :: Z. Peter Sawicki
Address Line One :: THE KINNEY & LANGE BUILDING
Address Line Two :: 312 South Third Street
City :: Minneapolis
State/Province :: MN
Postal or Zip Code :: 55415-1002
Telephone :: 612/339-1863
Fax :: 612/339-6580
E-Mail :: zpsawicki@kinney.com

Application Information

Title Line One :: Pasta filata cheese
Title Line Two ::
Total Drawing Sheets ::
Formal Drawings ::
Application Type :: Utility
Docket Number :: LL11.12-0050
Licensed - U S Government Agency ::
Contract Number ::
Grant Number ::
Secrecy Order in Parent Application ::

Representative Information

Representative Customer Number :: 00164

Continuity Information

This application is a ::
> Application One ::
Filing Date ::
Patent Number ::
which is a ::
>> Application Two ::
Filing Date ::
Patent Number ::

Priority Claimed ::

PASTA FILATA CHEESE

BACKGROUND OF THE INVENTION

The present invention relates to a process for manufacturing pasta filata cheese varieties and/or mozzarella-like products.

5 In the manufacture of pasta filata cheeses like Mozzarella, curd solids are typically heated in a hot water bath. When the individual curd particles begin to flow together the mass is subsequently pulled apart and folded back over to develop characteristic fibrous internal texture and smooth outer surfaces.

10 Spent hot water containing cheese solids, salt and energy is a major economic concern when considering commercial mozzarella cheese manufacture. Such losses represent lost manufacturing opportunity as well as high BOD, salinity, and thermal environmental pollution. Commercial mozzarella cheese facilities typically lose 5% curd fat during this unique pasta
15 filata manufacturing step. Only a portion of that fat loss is recoverable as whey cream. Approximately 0.045 gallon spent mixer water volume is developed per pound finished mozzarella cheese. A commercial mozzarella cheese manufacturer could expect to pay for disposal of 4,500 gallons mixer water with over 1,100 pounds dry solids (including 900 pounds sodium chloride) per
20 100,000 pounds finished cheese per day.

 Elimination or at least reduction in quantity of such spent hot water would be beneficial in terms of production cost (improved vat milk to finished cheese solids retention) as well as harm to the natural environment.

 Cheese compositional and functional variations continue to be a
25 major concern for both cheese manufacturers and users of the cheese. Controlling viable microbial count, fat content, moisture, salt content, acidity and refrigerated shelf stability improves cheese consistency. The pizza industry, as well as other users of cheese, continues to expect mozzarella cheese varieties and/or mozzarella-like styles of cheese that can be used over a broader range of
30 applications. A greater variety of pizzas, changes in oven styles, cooking

conditions and the like continue to be developed so as to maintain and/or increase the pizza maker's market-share. However, such changes affect the performance of the cheese. For example, the portioning of the cheese and/or amount of heat available during the cooking process to melt the cheese may be affected. By portioning is meant the ease of dividing into portions the cheese once it is melted. Portioning in turn relies on the cut integrity and firmness of the cheese when in the molten state. Changes in the amount of heat available for cooking result in differences in overall melt performance and flavor of the mozzarella cheese on the finished, baked pizza. Despite all the changes, it is still desired by the pizza industry that the portioning of the cheese improve, or at least not suffer, while the melt and flavor characteristics of the cheese remain the same.

Added to this, any changes that a cheese manufacturer may make in an attempt to achieve a more consistent functional product for a specific application may impact the handling and portioning of the cheese, such as when cutting a pizza. Thus a product which performs and meets the melt and flavor characteristics, yet does not handle/portion satisfactorily, is not acceptable. As regards portioning, in an attempt to control food costs, greater accuracy as to the free flowing, cut integrity of the product is required. Diced, sliced or shredded cheese that sticks to the cutting surface is difficult to handle. Such cheese requires more equipment cleanup and results in reduction in amount of useable cheese per purchased unit.

Upon baking the pizza, cheese is supposed to melt such that it loses its original shape and exhibits controlled "stringy" characteristics. However, such characteristics may vary from batch to batch. Cheeses made under conventional processes may melt too much or too little.

Process cheeses (non-pasta filata cheese) have more consistency from batch to batch, however, process cheese lacks the desired "stringy"

characteristics. Even when process cheese is formulated to improve its melt characteristics, process cheese typically does not release sufficient milk fat when melted in a pizza environment and a tough burnt cheese layer results.

Prior to this invention, manufacturers of mozzarella-like products have been limited in their control of performance characteristics of mozzarella cheese for use in a broad range of applications. The end user, especially the maker of pizza's, has had to accept cheese that may not be consistently uniform from vat to vat as well as at different times of the year.

The application of mozzarella cheese varieties and mozzarella-like products continue to grow and expand within the pizza industry, as well as its use in the food service/institutional industries. One reason for the continued growth is that the performance characteristics of mozzarella cheese even with its short comings have made it preferable over other varieties when used as an ingredient in some complex foods such as pizza.

One of mozzarella cheeses' most important attributes is its melting characteristics when baked as compared to other cheeses. These characteristics include melt down (time to melt), stretch, blistering/browning, and flavor. In general, melting is a function of the amount, rate, and/or source of heat over a specified time that is being transferred to the cheese during baking. Similar melt characteristics should be expected when keeping the amount and/or source of heat and the baking time constant for any application of mozzarella cheese. However, the natural variation in composition and seasonality of mozzarella cheese in terms of melt characteristics can differ substantially from one manufacturing vat to the next. It is even possible to have variations within a vat because of ongoing acid and protein changes during fermentation by viable microbial starters. Further variations to the mozzarella cheese are introduced by cooking conditions. For example, the style of pizza being prepared may vary the melt characteristics. Varying amounts of ingredients, thickness of crust and

types of ingredients all enter into changing the melting environment of the mozzarella cheese. Additionally, the type of oven used and the time of baking also has a significant impact on the amount and the source of heat available for melting the mozzarella cheese.

5

BRIEF SUMMARY OF THE INVENTION

The present invention includes a process of manufacturing a mozzarella or mozzarella-like cheese wherein a milk composition is pasteurized and formed into a coagulum. The coagulum is cut to separate curd from whey and the whey is drained therefrom. The curd is then heated preferably in a fluid-free state and mechanically worked until the curd forms a fibrous mass. The cheese is then formed into a selected shape.

10

Additionally, generally recognized as safe (GRAS) ingredients are added after the whey is drained but prior to heating the curd. In addition, the curd may be comminuted to a selected size after the whey is drained.

15

DETAILED DESCRIPTION

The present invention includes a process for making a pasta filata type cheese. Most common of such cheeses are mozzarella and provolone. Traditional manufacturing processes for making such cheese varieties are characterized by the fact that after the whey is drained off, the curd is immersed in hot water or hot whey and the submerged curd is worked and stretched while it is in a plastic condition to impart into the curd, the fibrous texture that characterizes such cheese varieties.

20

According to the process of the present invention, the working of the mozzarella curd in a hot liquid is eliminated. The working of the curd occurs in a substantially liquid-free environment. By liquid-free is meant that the curd is not immersed in a liquid such as water or whey. The curd does have water entrapped within and may have some surface wetness, but such moisture content is insufficient to be considered immersion.

25

In addition, the mozzarella curd is comminuted into fine granules after the curd is cut and the whey is drained. The curd is worked in a vessel at an elevated temperature in a dry state. The result is a pasta filata-cheese that has excellent texture and taste while retaining the fibrous texture that characterizes traditional made mozzarella cheese.

It has also been discovered that by the addition of various ingredients such as generally recognized as safe (GRAS) ingredients to the mozzarella curd before it has been heated results in improved control of analytical and functional characteristics. Such GRAS ingredients are typically added to process cheese and imitation cheeses. For example, an emulsifier can be added to the cheese curd after the curd is cut but before it is heated. Random variations can be noticeably reduced such that consistency in functional characteristics and production costs are improved.

Adding GRAS ingredients after cutting of the curd but before heating has been found not to be limited to any specific type of mozzarella process. The addition of the ingredients before heating is independent of the final form in which the mozzarella cheese is packaged, that is, whether it is formed into a block, diced/shredded, held refrigerated, and/or frozen. The mozzarella cheese produced by the process of the present invention produces a cheese that has a relatively longer storage period and while retaining its functional characteristics when baked on a pizza. Typically mozzarella shelf life is one month. After one month, traditional mozzarella loses some of its functional characteristics. The mozzarella cheese produced by the process of the present invention has a shelf life of at least two months and up to six months while still retaining its functional characteristics such as its fibrous texture, meltdown, stretch, blistering/browning, flavor and the like.

The difference between pasta filata cheese relative to process and imitation cheese varieties may be due, at least in part, to the cheese protein

component being only partially modified and under emulsified during heating and subsequent kneading. That partial modification may simply be a controlled removal of calcium bound to the coagulated cheese protein matrix. Sufficiently bound calcium could still remain intact within the matrix which results in

5 maintaining melt characteristics such as melt flow, stringiness, and cohesiveness. Process and imitation cheese formulations typically involve comparatively higher levels of emulsifying salts. Manufacture of process and imitation cheese varieties typically involve heat pasteurization temperatures above 170°F. The maximum heat treatment in the present invention is similar to

10 current practices for mozzarella and provolone cheese which is below pasteurization conditions.

The process of the present invention initially starts out in a traditional manner. The composition of fresh milk is adjusted to obtain the desired fat to protein ratio and fat content of the final cheese. Cow's milk is

15 preferred due to its availability, but other sources of milk traditionally used in making mozzarella cheese may also be used. For example, fresh cow's milk is standardized by fat removal to produce sweet cream and/or adding skim milk . Alternatively, recombined milk may be used as a starting milk composition. The recombined milk may be prepared from protein concentrate, acid casein,

20 caseinates, non-fat dry milk, whey, whey protein concentrate, whey protein isolate, cream, condensed milk or a combination of any two or more of the aforementioned ingredients.

The standardized cow's milk is then pasteurized and thereafter cooled to a range of 85° to 100°F. The milk is acidified before or after

25 pasteurization using any one of a number of substances or a combination thereof. The milk may be directly acidified with a mineral or organic acid or a microbial starter or any other acidulent. The milk is set (coagulated) with rennet or other suitable proteolytic agent.

5

10

15

25

or artificial flavors and anti-microbial agents. Such anti-microbial agents may be derived from natural (fermented) or artificial sources (sorbic acid).

Dairy ingredients may also be added prior to working of the curd. Dairy ingredients are added to enhance or change flavor, change protein to fat ratio or concentration. Exemplary dairy ingredients include dry, condensed, fluid, unripened, fermented, pH reduced: milk, cream, yogurt, skim solids or cheese.

Whether the ingredients are salt mixtures, non-dairy or dairy ingredients, they may be added in aqueous form anywhere from 5 to 50 % on a weight basis.

Preferably the curd has a finished moisture content of 20 to 80%, and most preferable 30 to 60 weight %. The moisture content of the curd may be adjusted in any number of ways including adding inert ingredients such as structural carbohydrates or silicates.

Prior to working, the curd mass is preferably comminuted by chopping or grinding. The ground, diced or chopped curd dimensions preferably range from the appearance of uniform paste to units as large as 1" x 6" x 15".

After grinding, the curd of the present invention is preferably worked in a dry environment. By working is meant that the curd is heated and then mechanically kneaded and stretched to a viscous molten state wherein the curd develops into a fibrous mass. By fibrous is meant that the curd develops texture. One characteristic of such a fibrous cheese mass is that the curd will form long threads when stretched. The curd is preferably heated to a temperature range of 130° to 160°F. Steamed-jacketed and/or infused vessels equipped with mechanical agitators (waterless cookers) are used to heat and work the curd blend. The curd blend may also be heated and worked in horizontal cookers that employ screw-augers to stir or work the curd while live steam is injected directly into the cheese. Another equipment option is direct

culinary steam injection into flowing curd mass. This is continuous process cheese cooker technology as opposed to individual batch equipment

Working the curd in a liquid-free environment results in several advantages unique to the present invention. First, loss of various solids such as protein, fat or additives is minimized if not eliminated since no effluent is created thereby increasing yield. Second, a liquid-free working environment has little if any costs associated with traditional liquid effluent disposal. Third, since there is no leaching of added ingredients into an effluent, more precise or controlled addition of ingredients is achieved. Fourth, enzymatic activity is reduced. In addition, secondary fermentation is also reduced.

The addition of GRAS ingredients may be done in a temperature range of between 20°F and 160°F. The blending of such ingredients can be done in a twin screw auger type mixer in which the augers overlap thereby insuring thorough mixing. The preferred capacity of such blending equipment is that it holds at least one batch of fresh curd plus the GRAS ingredients. A number of such blenders may be required to insure that the flow of the cheese curd is continuous to the subsequent heating and kneading steps. The number of blenders required is determined by dwell time in the blenders that is required to adequately mix all the ingredients and the through put required in the subsequent heating and kneading steps.

Heat treatments in the present invention are similar to current practices for traditional mozzarella and provolone cheese. Such molten mozzarella cheese texture development temperatures, commonly in the range of 135-150°F, are well below the pasteurization conditions seen in current manufacture of process cheese (in excess of 175°F for extended time periods). Various functional differences seen when comparing baked mozzarella to process cheese may in part be related to these initial manufacturing temperatures. The comparative functionality of baked mozzarella and process

cheeses may be a reflection of selectively modifying cheese protein, namely the chemistry of renneted casein. For proper baked mozzarella functionality (stretch and mouthfeel) such cheese protein structure may need to be limited to partial modification as opposed to the fully emulsified condition of process cheese protein.

A proper amount and/or ratio of protein-bound calcium to total casein may be required for adequate baked mozzarella melt, cohesive stretch and stringiness functionality. Too much calcium bound to mozzarella cheese casein (pH too high, excessive levels of available calcium) could lead to poor fat incorporation during manufacture, and then insufficient melt and burning when baked by the final customer. Too little bound calcium within the protein matrix could result in cheese with excessive melt and associated soft/soupy mouthfeel. Commercial shelf-life of mozzarella is commonly limited by these same apparent 'too little bound calcium' baked cheese attributes.

Selective fat release during mozzarella baking is another important characteristic and typically process cheese is too completely emulsified. Burnt process cheese on finished pizza is a common defect.

Salts and temperature levels outlined in the present application during mozzarella cheese manufacture are important distinctions relative to current process cheese practices. With the present invention, cheese manufacturers could modify baked mozzarella cheese functionalities such as melt, fat release, browning/blistering, stretch, string, and mouthfeel by changing the level of salts, and heating temperatures along with current fat, moisture, sodium chloride and pH control measures commonly known to one practicing in the art.

After the curd has been adequately worked, it is characterized by a uniform smooth appearance. The hot plastic curd mass is then transported via an extruder onto a chill roll or continuous belt. The resulting finished cheese

product is held on the chill roll or the continuous belt until sufficiently solidified. The cheese may be formed into either a circular, oval or rectangular cross-sectional shape between 0.25 inch to 15 inches in diameter or width or both in a horizontal or vertical plane. The chilled extrudate can then be divided
5 into finished selected dimensions. Alternatively, the finished cheese product may be directly extruded into packaging while hot, and then cooled. The packaged cheese may be held refrigerated or frozen for further use.

It has been discovered that the process of the present invention and the resulting products manufactured by the process are able to meet virtually
10 any desired performance characteristics under a more diverse set of applications. The following Examples are illustrative only and are not intended to limit the present invention in any way.

EXAMPLE I

Approximately 7,000 lbs. of Mozzarella cheese curd was
15 manufactured using the process described in the Bartz et al. U.S. Patent No.5,200,216 (hereby incorporated herein by reference). As described in the Bartz et al. patent, pasteurized cows' milk was converted into a cheese milk by fermenting the milk with lactic acid producing bacteria. The resulting product was a fresh curd that had a moisture content of 50.04%, 38.7% FDB (fat on a dry
20 basis), a pH of 5.29, and a salt content of 0.5%. Approximately 57.5 lbs of the fresh curd was removed for this example and the remaining fresh curd was finished into mozzarella cheese in the traditional manner wherein the curd was heated, kneaded and stretched in an aqueous solution, and thereafter extruded directly into cold brine. The approximately 57.5 lbs of fresh mozzarella curd was
25 blended with the following GRAS ingredients:

Ingredient	Weight (pounds)
skim cheese powder	2.00
salt (sodium chloride)	0.50
sodium citrate dihydrate	0.50
anhydrous citric acid	0.15

5 The mozzarella curd (which was unsalted/0.2% salt) was blended
 in a pilot scale twin screw auger blender/cooker (Custom Stainless Equipment
 Company, Santa Rosa, CA/Models: EDB.0718.FVX) for approximately 20
 10 minutes. The curd was then heated from 99°F to 150°F within four (4) minutes
 using a combination of indirect and direct steam injection. The resulting cheese
 had a weight of approximately 61.6 lb and had a wet fat content of 17.76%, a
 moisture content of 48.61%, an FDB of 34.6%, a salt content of 1.72% and a
 pH of 5.29. The cheese produced by the process of this invention was
 15 comparable in cold flavor, cold shred identity, hot melt, oil, color, stretch, fiber
 and chewy texture similar to that portion processed in the traditional manner.

EXAMPLE II

A mozzarella cheese curd was manufactured by the process
 described in the Bartz et al. U.S. Patent No. 5,200,216 which is hereby
 20 incorporated by reference. As described in the Bartz et al. patent, pasteurized
 cows' milk was converted into a cheese milk by fermenting the milk with lactic
 acid producing bacteria. A portion of the fresh curd was processed (finished) in
 a traditional manner which included heating, kneading and stretching in an
 aqueous solution, and then extruded into its final form. Another portion of the
 25 fresh cheese which was approximately 600 lb was further finished using the
 process of the present invention. The fresh curd had a 49.0% moisture content,
 39.2% FDB, a pH of 5.25, and a salt content of 0.2% and a wet fat content of
 20.0%

The curd was blended with the following ingredients:

Ingredient	Weight (pounds)
42% fat whey cream	33.00
skim cheese powder	18.00
salt (sodium chloride)	7.00
sodium citrate dihydrate	3.50
anhydrous citric acid	2.00

10 The curd and the above ingredients were blended in a commercial scale twin screw auger blender/cooker (Custom Stainless Equipment Company, Santa Rosa, California/Model: CDB.1845) for approximately 30 minutes and then the curd was heated from approximately 99°F to 150°F within 60 seconds using direct culinary steam injection.

15 The resulting cheese weighed 717.2 lb and had a wet fat content of 20.81%, a moisture content of 47.22%, an FDB of 39.43%, a pH of 5.35 and a salt content of 1.6%. The dry cream, skim cheese powder and whey cream were added to compensate for culinary steam condensate plus to adjust fat as a percentage of total cheese solids. When compared to the portion of the cheese
20 processed in the traditional manner, the cheese according to this example had similar analytical composition, cold flavor, cold shred identity, hot melt, oil release, color, stretch, fiber and chewy texture.

EXAMPLE III

25 A full fat cheese curd was manufactured as described in the Code of Federal Regulations 21.133.113. Pasteurized cow's milk was converted into a cheese milk by fermenting the milk with lactic acid-producing bacteria. The resulting curd had a 44.0% moisture content, 52% FDB, a pH of 5.25 and a salt content of 1.5%. A portion of the curd was segregated and was blended with

GRAS ingredients such that the finished cheese dry fat and moisture composition would coincide with typical provolone composition requirements as described in the Code of Federal Regulations 21.133.181. The portion of segregated curd was approximately 680 lb of full fat curd having a wet fat content of 29.0%. The following ingredients were added to the curd:

Ingredient	Weight (pounds)
Skim cheese powder	40.00
Sodium citrate dihydrate	3.00
Anhydrous Citric acid	1.00

The ingredients and the curd were mixed in a commercial-scale, twin screw auger, blender/cooker (Custom Stainless Equipment, Santa Rosa, California/Model: CDB.1845) for approximately 30 minutes. The mixed curd was then heated from approximately 90°F to 150°F within 70 seconds using direct culinary steam injection. The finished cheese product weighed 754.2 lb and had a wet fat content of 26.25%, a moisture content of 44.38%, an FDB of 47.2%, and a salt content of 1.71%. The curd had a similar cold flavor, cold shred identity, hot melt, oil release, color, stretch, fiber and chewy texture relative to typical provolone cheese.

Although the present invention has been described with reference to preferred embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention.

CLAIM(S):

1. A process of manufacturing a pasta filata cheese or a mozzarella-like cheese comprising:
 - providing a milk composition having a selected protein and fat composition;
 - pasteurizing the milk composition;
 - forming a coagulum from the milk composition;
 - cutting the coagulum to separate curd and whey;
 - draining the whey from the curd;
 - heating the curd without aqueous immersion to an approximate temperature range of 130°F to 160°F;
 - mechanically working the curd into a fibrous mass; and
 - forming the cheese into a selected shape.
2. The process of claim 1 wherein a GRAS ingredient is mixed into the curd prior to mechanical working of the curd.
3. The process of claim 1 wherein the curd is comminuted to a selected size.
4. The process of claim 1 wherein the coagulum is heated after being cut to facilitate moisture removal from the curd.
5. The process of claim 1 wherein the milk composition is fresh milk.
6. The process of claim 1 wherein the milk composition is recombined milk.

7. The process of claim 6 wherein the recombined milk is prepared from either protein concentrate, acid casein, rennet casein, caseinates, nonfat dry milk, whey, whey protein concentrate, whey protein isolate, cream, or condensed milk or any combination thereof.
8. The process of claim 1 and further adding a salt composition to the curd prior to mechanical working.
9. The process of claim 8 wherein the salt composition includes an alkaline earth salt of simple or complex chlorides, sulfates, phosphates or citrates used in the manufacture of process cheese, cheese food, cheese spread, cheese sauce or imitation or analog cheeses.
10. The process of claim 9 wherein the alkaline earth salt is a sodium, potassium, calcium, magnesium or salt.
11. The process of claim 1 wherein a non dairy ingredient is added to the curd prior to mechanical working.
12. The process of claim 11 wherein the non-dairy ingredient is a functional carbohydrate, a lipase, a protease, a mineral acid, an organic acid, a structural protein, or an antimicrobial agent or a combination thereof.
13. The process of claim 1 wherein a dairy ingredient is added to the curd prior to mechanical working.

0947831-010604

14. The process of claim 13 wherein the dairy ingredient is either a milk, cream, yogurt, skim solids, or cheese that is dry, condensed, fluid, unripened, fermented or pH reduced or any combination thereof.
15. The process of claim 11 wherein the nondairy ingredient if in dry form is mixed in an aqueous solution containing about five to fifty percent by weight of the dairy ingredient.
16. The process of claim 9 wherein the salt composition if in dry form is mixed in an aqueous solution containing about five to fifty percent by weight of the salt composition.
17. The process of claim 14 wherein if the dairy ingredient is in dry form is mixed in an aqueous solution containing about five to fifty weight percent of the dairy ingredient.
18. The process of claim 1 wherein an emulsifying salt composition is added to the curd via a starter culture medium.
19. The process of claim 1 wherein a non-dairy ingredient is added to the curd via a starter culture medium.
20. The process of claim 1 wherein a dairy ingredient is added to the curd via a starter culture medium.
21. The process of claim 1 wherein the cheese has a final moisture content in the range of about 20 to about 90 weight percent.

22. The process of claim 21 wherein the cheese has a final moisture content in the range of about 30 to 60 weight percent.
23. The process of claim 21 wherein the cheese final moisture content is adjustable by the addition of inert ingredients.
24. The process of claim 23 wherein the inert ingredients are either structural carbohydrates or silicates or a combination thereof.
25. The process of claim 1 wherein the mechanical working of the curd is done in a waterless cooker.
26. The process of claim 1 and further including:
cooling the cheese after the cheese is formed into the selected shape.
27. The process of claim 26 and further packaging the cooled cheese.
28. The process of claim 26 wherein the cheese is formed into either a circular, oval or rectangular cross-sectional shape between 0.25 inch to 15 inches in diameter or width or both in a horizontal or vertical plane.
29. The process of claim 26 wherein the cheese is formed into shape by being extruded directly into packaging.
30. The process of claim 1 wherein pH of the curd is adjusted after the whey is drained to a pH range of approximately 5.0 to 5.4.

31. A product produced by the process of claim 1 characterized by retention of mozzarella-like stringy texture even after two months from creation.

32. A process of manufacturing a pasta filata cheese or a mozzarella-like cheese comprising:

providing a milk composition having a selected protein and fat composition;
pasteurizing the milk composition;
forming a coagulum from the milk composition;
cutting the coagulum to separate curd and whey;
draining the whey from the curd;
heating the curd to an approximate temperature range of 130°F to 160°F;
adding phosphate or citrate emulsifying salts or a combination thereof to the curd;
mechanically working the curd into a fibrous mass; and
forming the cheese into a selected shape.

33. The process of claim 32 wherein the emulsifying salt is an alkaline earth salt.

34. The process of claim 33 wherein the alkaline earth salt is a sodium, potassium, calcium, magnesium salt.

35. The process of claim 32 wherein the salt is mixed into the curd in the form of an aqueous solution containing about 5 to 50% of the salt based on the weight of the solution.

36. The process of claim 32 wherein the cheese has a finished moisture content in the range of 40 to 60% after being formed into the selected shape.

37. The process of claim 32 wherein the temperature of the curd is in the approximate range of 20 to 160°F when adding the emulsifying salts.

38. The process of claim 35 wherein the aqueous solution is mixed into the curd for a period of time ranging from approximately 2 to 60 minutes prior to heating the curd.

39. The process of claim 32 wherein the cheese is formed into the selected shape by being extruded into packaging.

40. The process of claim 32 wherein forming the cheese into the selected shape includes forming the cheese into an intermediate shaped extrudate by extrusion onto a chill roll or continuous belt.

41. The process of claim 32 wherein the cheese produced by the process of claim 30 is characterized by a shelf life of up to six months.

42. A product produced by the process of claim 32 characterized by retention of mozzarella-like stringy texture even after two months from creation.

43. A process of manufacturing a pasta filata cheese or a mozzarella-like cheese comprising:

providing a milk composition having a selected protein and fat composition;

pasteurizing the milk composition;

forming a coagulum from the milk composition;
cutting the coagulum to separate curd and whey;
draining the whey from the curd;
adding generally recognized as safe ingredients into the curd in
amounts effective to obtain selected compositional or
functional properties in a final cheese product;
heating the curd to a range of approximately 130 to 160°F;
mechanically working the cheese curd into a fibrous mass; and
forming the cheese into a selected shape.

44. The process of claim 43 wherein heating the curd to approximately 130 to 160°F and mechanically working the cheese into a fibrous mass are separate and distinct steps.

45. The process of claim 43 wherein the cheese is formed into a selected shape by cooling.

46. The process of claim 43 wherein the cheese is packaged hot and then cooled.

47. The process of claim 43 wherein the generally recognized as safe ingredient includes a salt composition comprising of simple or complex chlorides or both, sulfates, phosphates or citrate cheese emulsifying salts or combination thereof.

48. The process of claim 47 wherein the emulsifying salt is an alkaline earth salt.

49. The process of claim 48 wherein the alkaline earth salt is sodium, potassium, calcium, magnesium or salt.

50. The process of claim 43 wherein the generally recognized as safe ingredients comprise non-dairy ingredients that include either functional carbohydrates, lipase, protease, mineral acid, organic acid, structural protein, or anti-microbial agents, or any combination thereof.

51. The process of claim 43 wherein the generally recognized as safe ingredients comprise dairy ingredients that include either a milk, cream, yogurt, skim solids, or cheese that is dried, condensed, fluid, unripened, fermented or pH reduced or any combination thereof.

52. The process of claim 50 wherein the non-dairy ingredients are in dry form and are mixed in an aqueous solution containing about 5 to 50 weight percent of the non-dairy ingredient.

53. The process of claim 51 wherein the dairy ingredient are in a dry form and are mixed in an aqueous solution containing about 5 to 50 weight percent of the dairy ingredient.

54. The process of claim 47 wherein the salt composition is in a dry form and is mixed in an aqueous solution containing about 5 to 50 weight percent of the salt composition.

55. The process of claim 43 wherein the cheese has a finished moisture content in the range of about 40 to 60 weight percent.

56. The process of claim 43 wherein the cheese is formed into either a circular, oval or rectangular cross-sectional shape between 0.25 inch to 15 inch diameter or with or both in a horizontal or vertical plain.

57. The process of claim 42 wherein the cheese is formed into shape by being extruded directly into packaging.

58. The process of claim 43 wherein the cheese is characterized by a shelf life of up to six months.

59. A product produced by the process of claim 43 characterized by retention of mozzarella-like stringy texture even after two months from creation.

60. A process of manufacturing a pasta filata cheese or a mozzarella-like cheese comprising:

- providing a milk composition having a selected protein and fat composition;
- adding an acidifying agent to the milk composition;
- pasteurizing the milk composition after acidification;
- cutting the coagulum to separate curd and whey;
- draining the whey from the curd;
- heating the curd to an approximate temperature range of 130°F to 160°F;
- adding phosphate or citrate emulsifying salt or a combination therefore to the curd;
- mechanically working the curd into a fibrous mass; and
- forming the cheese into a selected shape.

61. The process of claim 60 wherein the emulsifying salt is an alkaline earth salt.
62. The process of claim 61 wherein the alkaline earth salt is a sodium, potassium, calcium, magnesium or salt.
63. The process of claim 60 wherein the salt is mixed into the curd in the form of aqueous solution containing about 5 to 50% of the salt, based on the weight of the solution.
64. The process of claim 60 wherein the cheese has a moisture content in the range of 40 to 60% after being formed into the selected shape.
65. The process of claim 60 wherein the temperature of the curd is in the approximate range of 20 to 160°F when adding the emulsifying salts.
66. The process of claim 64 wherein the aqueous solution is mixed into the curd for a period of time ranging from prior to heating the curd.
67. The process of claim 60 wherein the cheese is formed into the selected shape by being extruded into packaging.
68. The process of claim 60 wherein forming the cheese into the selected shape includes forming the cheese into an intermediate shaped extrudate by extrusion onto a chill roll or continuous belt.

69. The process of claim 60 wherein the cheese produced by the process of claim 30 is characterized by a shelf life of up to six months.

70. An improved process of manufacturing a pasta filata cheese or a mozzarella-like cheese, the improvement comprising:

after a coagulum is formed from a milk composition, and the coagulum cut to separate the curd and whey and the whey drained from the curd, heating the curd in an aqueous free environment to an approximate temperature range of 130°F to 160°F and mechanically working the curd in the aqueous free environment until a mozzarella-type texture is achieved.

71. The process of claim 70 wherein the curd is comminuted to a selected size prior to heating.

72. The process of claim 70 wherein the coagulum is heated after being cut to facilitate further moisture removal from the curd.

73. The process of claim 72 wherein the pH of the drained curd is adjusted to a range of 5.2 to 5.4.

74. The process of claim 70 wherein a GRAS ingredient is mixed into the curd prior to mechanical working of the curd.

75. The process of claim 74 wherein the GRAS ingredient is either a cheese emulsifying salt, a non-dairy ingredient, or a dairy ingredient.

76. The process of claim 75 wherein the emulsifying salt includes simple or complex chlorides, phosphates or citrates or a combination thereof.
77. The process of claim 75 wherein the non-dairy ingredient includes a functional carbohydrate, a lipase, a protease, a mineral acid, an organic acid, a structural protein or an antimicrobial agent or a combination thereof.
78. The process of claim 75 wherein the dairy ingredient is either a milk, cream, yogurt, skim solids, or cheese that is dry, condensed, fluid, unripened, fermented or pH reduced or any combination thereof.
79. The process of claim 75 wherein the emulsifying salt, the dairy ingredient or the non-dairy ingredient if in dry form is mixed in an aqueous solution containing about 5 to 50% by weight of the emulsifying salt, the dairy ingredient or the non-dairy ingredient.
80. A product produced by the process of claim 60 characterized by retention of mozzarella-like stringy texture even after two months from creation.

PASTA FILATA CHEESE MANUFACTURE

ABSTRACT OF THE DISCLOSURE

The present invention includes a process of manufacturing a mozzarella variety of cheese or a mozzarella-like cheese wherein a milk composition is pasteurized and formed into a coagulum. The coagulum is cut to separate curd from whey and the whey is drained therefrom. The curd is then heated preferably in a liquid-free environment and mechanically worked until the curd forms a fibrous mass. The cheese is then formed into a selected shape. Additionally, generally recognized as safe (GRAS) ingredients are added after the whey is drained but prior to heating the curd. In addition, the curd may be comminuted to a selected size after the whey is drained.


G \ZPS\PATFILE\LL11-12\050APP


U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)


DIRECT ALL CORRESPONDENCE TO:

Name	Z. Peter Sawicki
Address	Kinney & Lange, P.A. THE KINNEY & LANGE BUILDING 312 South Third Street Minneapolis, Minnesota 55415 United States
Telephone	(612) 339-1863
Fax	(612) 339-6580

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Sole or First Inventor:	
Given Name (First and middle (if any))	Family Name or Surname
Donald G.	Dahlstrom
Inventor's signature	 Date: 05 Jan 2000
Residence	Oneida, Wisconsin Citizenship: U.S.A.
Post Office Address	4455 North Pine Tree Road
City, State, Country	Oneida, Wisconsin 55449, U.S.A.

Second Inventor:	
Given Name (First and middle (if any))	Family Name or Surname
James	Wiegand
Inventor's signature	 Date: 1/3/00
Residence	Circle Pines, Minnesota Citizenship: U.S.A.
Post Office Address	2nd Pleasantview Lane
City, State, Country	Circle Pines, Minnesota 55014, U.S.A.

Third Inventor:			
Given Name (First and middle (if any))		Family Name or Surname	
William R.		Aimutis	
Inventor's signature	 Date: 12/27/99		
Residence	Blaine, Minnesota		Citizenship: U.S.A.
Post Office Address	3126 Rodeo Drive NE		
City, State, Country	Blaine, Minnesota 55449		

POWER OF ATTORNEY

Attorney Docket No.

LL11.12-0050

First Named Inventor : Donald Dahlstrom et al.

Title : PASTA FILATA CHEESE

In the patent application:

X identified above (and submitted to the Patent and Trademark Office herewith).

— filed on _____ as Application No. _____ .

I appoint the attorneys and agents associated with Customer Number 00164 to prosecute the patent application identified above and to transact all business in the Patent and Trademark Office connected therewith, including full power of association, substitution and revocation.

I ratify all prior actions taken by Kinney & Lange, P.A. or the attorneys and agents mentioned above in connection with the prosecution of the above-mentioned patent application.

I authorize Kinney & Lange, P.A. to mark the appropriate space above and to insert the filing date and application number of the application, as appropriate.

Please address all correspondence and telephone calls to Z. Peter Sawicki at:

KINNEY & LANGE, P.A.
THE KINNEY & LANGE BUILDING
312 South Third Street
Minneapolis, Minnesota 55415-1002
Phone: (612) 339-1863 Fax: (612) 339-6580


LAND O'LAKES, INC.

Signature: _____

Dated: _____

Printed Name: _____

Title: _____



William R. Aimotis

Vice President

12/27/99